

540,183

Rec'd 10/54 0183  
T/PTO 20 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number  
WO 2004/057844 A1(51) International Patent Classification<sup>7</sup>:  
G06F 3/033

H04M 1/23,

(74) Common Representative: KONINKLIJKE PHILIPS  
ELECTRONICS N.V.; Intellectual Property & Standards,  
c/o Slobod, Jack, D., P.O. Box 3001, Briarcliff Manor, NY  
10510-8001 (US).

(21) International Application Number:

PCT/IB2003/005964

(22) International Filing Date:

11 December 2003 (11.12.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/435,234

20 December 2002 (20.12.2002)

US

(71) Applicant (for all designated States except US): KONIN-  
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,  
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,  
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a  
patent (Rule 4.17(ii)) for all designations

## Published:

— with international search report


(71) Applicant (for AE only): U.S. PHILIPS CORPORA-  
TION [US/US]; 1251 Avenue of the Americas, New York,  
NY 10020 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): DESTURA, Galileo,  
J.A. [NL/NL]; P.O. Box 220, NL-5600 AE Eindhoven  
(NL).For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR COMPOSING SMS MESSAGE

21

(57) Abstract: A user of a mobile phone  
(20) composes a message on a display  
screen (21) of the mobile phone (20) by a  
selective application of various load levels  
upon various areas of the display screen  
(21) that correspond to keys of a virtual  
keypad (23). An application of a load  
upon a localized area of one of the keys  
will display one of a plurality of characters  
associated with the respective key. A  
sensed and measured level of the applied  
load determines which of the characters is  
displayed on the display screen (21).

WO 2004/057844 A1

# METHOD AND DEVICE FOR COMPOSING SMS MESSAGE

The present invention generally relates to wireless communication devices. The present invention specifically relates to a Short Messaging Service ("SMS") of a mobile phone.

FIG. 1 illustrates a mobile phone 10 having a standard keypad 11 and a display screen 12. The following TABLE 1 lists the number of button presses associated with a display of each alphabetic character, numeric character and symbolic character of keypad 11:

TABLE 1

<u>1 PRESS</u>	<u>2 PRESSES</u>	<u>3 PRESSES</u>	<u>4 PRESSES</u>	<u>5 PRESSES</u>
1				
A	B	C	2	
D	E	F	3	
G	H	I	4	
J	K	L	5	
M	N	O	6	
P	Q	R	S	7
T	U	V	8	
W	X	Y	Z	9
*				
0				
#				

Consequently, sending a message of "HAVE A NICE DAY" as illustrated would require a user of mobile phone 10 to perform a total of twenty-seven (27) key presses [H(2P), A(1P), V(3P), E(2P), SPACE, A(1P), SPACE, N(2P), I(3P), C(3P), E(2P), SPACE, D(1P), A(1P), and Y(3P)]. Clearly, sending longer and/or more elaborate messages can be time consuming and burdensome for a user of mobile phone 10.

One form of the present invention is a wireless communication device (e.g., a mobile phone, a personal data assistant, etc.) for composing a message. The device comprises a display screen and a virtual keypad having a plurality of keys displayed on the

display screen. The virtual keypad includes a first key operable to display a first character associated with the first key within the message as displayed on the display screen in response to an application of a first load level upon a localized area of the display screen corresponding to the first key. The first key is further operable to display a second character associated with the first key within the message as displayed on the display screen in response to an application of a second load level upon the localized area of the display screen corresponding to the first key.

A second form of the present invention is a method of operating a wireless communication device in composing a message. The wireless communication device includes a display screen and a virtual keypad having a plurality of keys displayed on the display screen. First, an application of a load upon a localized area of the display screen corresponding to a first key of the virtual keypad is sensed and measured. Second, a first character associated with the first key is displayed within the message in response to the load equating a first load level. Third, a second character associated with the first key is displayed within the message in response to the load equating a second load level.

The foregoing forms as well as other forms, features and advantages of the present invention will become further apparent from the following detailed description of the presently preferred embodiments, read in conjunction with the accompanying drawings. The detailed description and drawings are merely illustrative of the present invention rather than limiting, the scope of the present invention being defined by the appended claims and equivalents thereof.

FIG. 1 illustrates a front view of a standard mobile phone;

FIG. 2 illustrates a side view of one embodiment of a mobile phone in accordance with the present invention;

FIG. 3 illustrates a front view of one embodiment of a display screen and a virtual keypad of the mobile phone illustrated in FIG. 2;

FIG. 4 illustrates one embodiment of a capacitance profile of the display screen illustrated in FIG. 3; and

FIG. 5 illustrates one embodiment of a cross sectional capacitance of a key of the virtual keypad illustrated in FIG. 3.

FIG. 2 illustrates a mobile phone 20 having a touch sensitive display screen 21 and a standard keypad 22. The touch sensitive display screen 21 is responsive to an application

of a load upon an area of display screen 21, such as, for example, the downward load being applied to display screen 21 via a stylus 30 as illustrated in FIG. 2. The downward load may be applied by other instruments as would occur to those having ordinary skill in the art, such as, for example, a finger of a user of mobile phone 20. In one embodiment, the touch sensitive display screen 21 is fabricated and operated in accordance European Patent Application Serial No. 02076461.9, entitled "Touch Sensitive Display Device" and filed April 15, 2002, which is hereby incorporated by reference.

FIG. 3 illustrates a display of a virtual keypad 23 on the touch sensitive display screen 21. Each illustrated key of the virtual keypad 23 has one or more associated characters (e.g., alphabetic, numeric or symbolic). Each key of virtual keypad 23 is further assigned to a localized area of the touch sensitive display screen 21, such as, for example, the area of display screen 21 directly above a key. Accordingly, when a user of mobile phone 20 desires to compose a message, the user sequentially applies various load(s) in the localized area(s) corresponding to the key(s) required to the compose the message. For any given key, a sensed and measured level of the load determines which character associated with the key will be displayed within the message on display screen 21.

FIG. 4 illustrates a profile of a capacitive-based embodiment of the touch sensitive display screen 21. From FIG. 4, coordinates of a localized area of display screen 21 for each key can be ascertained. A capacitance of each key equals a base level in the absence of an application of a load upon a corresponding localized area, such as, for example, 0.5 pF as illustrated in FIG. 4. A capacitance of each key increases upon an application of a load upon a corresponding localized area, such as, for example, the profile of capacitance of key "jkl5" as illustrated in FIG. 4. The degree to which the capacitance increases is indicative of the amount of load being applied to the corresponding localized area. Each character associated with a key is further associated with a different load level to thereby ascertain when the user of mobile phone 20 desires to include a specific character within the message on display screen 21.

FIG. 5 illustrates a cross-sectional view of five (5) load levels representative of an application of five (5) different load levels upon a localized area of key of the virtual keypad 23 (FIG. 3). The five (5) load levels include a 10% increase in capacitance of a key, a 30% increase in capacitance of a key, a 50% increase in capacitance of a key, a 80% increase in capacitance of a key, and a 100% increase in capacitance of a key. The

following TABLE 2 exemplarily lists an association of each load level with one or more characters:

TABLE 2

<u>10%</u>	<u>30%</u>	<u>50%</u>	<u>80%</u>	<u>100%</u>
1				
A	B	C	2	
D	E	F	3	
G	H	I	4	
J	K	L	5	
M	N	O	6	
P	Q	R	S	7
T	U	V	8	
W	X	Y	Z	9
*				
0				
#				

Consequently, sending a message of "HAVE A NICE DAY" as illustrated would require a user of mobile phone 10 to perform a total of fifteen (15) key presses [H(1P), A(1P), V(1P), E(1P), SPACE, A(1P), SPACE, N(1P), I(1P), C(1P), E(1P), SPACE, D(1P), A(1P), and Y(1P)], for a total decrease of twelve (12) presses. Clearly, sending longer and/or more elaborate messages will be less time consuming and burdensome for a user of mobile phone 20.

In one embodiment, each load level of TABLE 1 represents a minimum load level within a range encompassing the load level. Thus, a measurement of a load equates the 10% load level when a load measurement LM is within a range of  $10\% \leq LM < 30\%$ , a measurement of a load equates the 30% load level when a load measurement LM is within a range of  $30\% \leq LM < 50\%$ , and so on and so on.

In a second embodiment, each load level of TABLE 1 represents a maximum load level within a range encompassing the load level. Thus, a measurement of a load equates the 10% load level when a load measurement LM is within a range of  $0\% < LM \leq 10\%$ , a

measurement of a load equates the 30% load level when a load measurement LM is within a range of  $10\% < LM \leq 30\%$ , and so on and so on.

In a third embodiment, each load level of TABLE 1 represents load level within a range encompassing the load level. Thus, a measurement of a load equates the 10% load level when a load measurement LM is within a range of  $0\% < LM \leq 20\%$ , a measurement of a load equates the 30% load level when a load measurement LM is within a range of  $20\% < LM \leq 40\%$ , and so on and so on.

The number of load levels associated with a key is without limit. The following TABLE 3 exemplarily lists another association of load levels with one or more characters:

TABLE 3

<u>10%</u>	<u>20%</u>	<u>30%</u>	<u>40%</u>	<u>50%</u>	<u>60%</u>	<u>80%</u>	<u>90%</u>	<u>100%</u>
1								
A	a	B	b	C	c	2		
D	d	E	e	F	f	3		
G	g	H	h	I	i	4		
J	j	K	k	L	l	5		
M	m	N	n	O	o	6		
P	p	Q	q	R	r	S	s	7
T	t	U	u	V	v	8		
W	w	X	x	Y	y	Z	z	9
*								
0								
#								

It is important to note that FIGS. 2-5 illustrate specific applications and embodiments of the present invention, and is not intended to limit the scope of the present disclosure or claims to that which is presented therein. Upon reading the specification and reviewing the drawings hereof, it will become immediately obvious to those skilled in the art that myriad other embodiments of the present invention are possible, and that such embodiments are contemplated and fall within the scope of the presently claimed invention.

While the embodiments of the invention disclosed herein are presently considered to be preferred, various changes and modifications can be made without departing from the spirit and scope of the invention. The scope of the invention is indicated in the appended claims, and all changes that come within the meaning and range of equivalents are intended to be embraced therein.

## CLAIMS:

1. A wireless communication device (20) for composing a message, said device (20) comprising:
  - a display screen (21); and
  - a virtual keypad (23) having a plurality of keys displayed on said display screen (21),wherein said virtual keypad (23) includes a first key operable to display a first character associated with said first key within the message as displayed on said display screen (21) in response to an application of a first load level upon a localized area of said display screen (21) corresponding to said first key, and
  - wherein said first key is further operable to display a second character associated with said first key within the message as displayed on said display screen (21) in response to an application of a second load level upon the localized area of said display screen (21) corresponding to said first key.
2. The wireless communication device (20) of claim 1, wherein said first key is further operable to display a third character associated with said first key within the message as displayed on said display screen (21) in response to an application of a third load level upon the localized area of said display screen (21) corresponding to said first key.
3. The wireless communication device (20) of claim 2, wherein said first key is further operable to display a fourth character associated with said first key within the message as displayed on said display screen (21) in response to an application of a fourth load level upon the localized area of said display screen (21) corresponding to said first key.
4. The wireless communication device (20) of claim 5, wherein said first key is further operable to display a fifth character associated with said first key within the message as displayed on said display screen (21) in response to an application of a fifth load level upon the localized area of said display screen (21) corresponding to said first key.



5. In a wireless communication device (20) including a display screen (21) and a virtual keypad (23) having a plurality of keys displayed on the display screen (21), a method of composing a message, said method comprising:

sensing and measuring an application of a load upon a localized area of the display screen (21) corresponding to a first key of the virtual keypad (23);

displaying a first character associated with the first key within the message as displayed on the display screen (21) in response to a measurement of the load equating a first load level; and

displaying a second character associated with the first key within the message as displayed on the display screen (21) in response to a measurement of the load equating a second load level.

6. The method of claim 5, further comprising:

displaying a third character associated with the first key within the message as displayed on the display screen (21) in response to a measurement of the load equating a third load level.

7. The method of claim 6, further comprising:

displaying a fourth character associated with the first key within the message as displayed on the display screen (21) in response to a measurement of the load equating a fourth load level.

8. The method of claim 7, further comprising:

displaying a fifth character associated with the first key within the message as displayed on the display screen (21) in response to a measurement of the load equating a fifth load level.




FIG. 1




FIG. 2





FIG. 3



**FIG. 4**




FIG. 4A




FIG. 5

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/05964

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04M1/23 G06F3/033

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 H04M G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	US 2003/122779 A1 (GOLDENBERG ALEX S ET AL) 3 July 2003 (2003-07-03) abstract paragraph '0052! - paragraph '0058!; figure 5	1-8
X	WO 97 30386 A (KATO SYUNJI ;KATO YOSHIYA (JP); MISAWA HOMES CO (JP)) 21 August 1997 (1997-08-21) abstract; figures 1,2,11 page 41, line 19 - line 22; claims 1,4; figure 19	1-8
A	WO 02 088920 A (KATO SYUNJI ;MISAWA HOMES CO (JP)) 7 November 2002 (2002-11-07) abstract; figures 22-28	1-8
	--- -/-- ---	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

31 March 2004

Date of mailing of the international search report

08/04/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pascual Vallés, E

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/05964

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DE 198 49 460 A (VOELCKERS OLIVER)  4 May 2000 (2000-05-04)  abstract; figures 1-3  column 2, line 43 - line 16  column 4, line 31 - line 37  -----</p>	1-8



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 03/05964

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2003122779	A1	03-07-2003	US 2004012560 A1	22-01-2004
WO 9730386	A	21-08-1997	JP 2000035857 A	02-02-2000
			AU 1673497 A	02-09-1997
			CA 2246682 A1	21-08-1997
			CN 1216620 A , B	12-05-1999
			DE 69704018 D1	08-03-2001
			DE 69704018 T2	22-05-2003
			EP 0882259 A1	09-12-1998
			WO 9730386 A1	21-08-1997
			TW 413779 B	01-12-2000
			US 6295052 B1	25-09-2001
WO 02088920	A	07-11-2002	EP 1383034 A1	21-01-2004
			WO 02088920 A1	07-11-2002
			JP 2003015808 A	17-01-2003
DE 19849460	A	04-05-2000	DE 19849460 A1	04-05-2000
			WO 0025500 A1	04-05-2000
			EP 1042897 A1	11-10-2000
			JP 2002528831 T	03-09-2002